

## IMPRESORA TÉRMICA PARA RECIBOS BLUETOOTH

**2C-P80-C**



## CARACTERÍSTICAS

- Ancho del papel de 80mm (3 Pulgadas)
- Conexión vía Bluetooth y USB
- Calidad de impresión 203DPI,8 dots/mm
- Velocidad de impresión 70-80mm/s
- Bateria: 1500mAh recargable li-ion
- Compatible: ESC/POS
- Imprime Códigos de Barras: 1D, 2D-QR
- Compatible: Windows, Android, Ubuntu, MAC Os, Opus, Linux

## DESCRIPCIÓN TÉCNICA

<b>Printing method</b>	Thermal printing
<b>Resolution</b>	203DPI,8 dots/mm
<b>Printing Width</b>	79mm (384 dots)
<b>Printing speed</b>	70-80mm/s
<b>Interfaces</b>	USB + Bluetooth
<b>Power Supply Input</b>	100-240V AC,50-60HZ
<b>Output</b>	12V DC-3.0A
<b>External Only</b>	Power Adaptor
<b>PaperType</b>	Standard Thermal Receipt Paper
<b>Paper Width</b>	80.mm (3 Inch)
<b>Thickness</b>	0.056~0.1mm
<b>Paper Diameter</b>	40mm Max
<b>Character</b>	Chinese GB18030 24×24 Words, figures ASCII 9×17,12×24
<b>Support Optional</b>	Chinese, Korean, Japanese, English

<b>Code Page</b>	56 kinds of code page
<b>Reliability TPH life</b>	50km
<b>Motor Life</b>	360,000 hours
<b>OS compatibility</b>	Windows, Android, Ubuntu, MAC Os, Opus, Linux
<b>Bar Codes</b>	1D -> UPC-A, UPC-E, EAN-8, EAN13, CODE39, ITF CODEBAR, CODE128, CODE93 2D -> PDF417, QR Code
<b>Paper loading</b>	Easy paper loading
<b>Paper cutting</b>	Manual or Automatically Cut Paper
<b>Operating condition</b>	-10°C ~ 50°C, 25% ~ 80%RH
<b>Storage condition</b>	~40°C ~ 70°C, ≤93%RH (40°C)
<b>Outline dimension</b>	97.5mm×75mm×48mm (W×L×H)
<b>Weight</b>	0.2Kg
<b>Battery</b>	1500mAh Rechargeable li-ion