

IMPRESORA MATRICIAL PARA TICKETS

2C-MP76-01


CARACTERÍSTICAS

- Impresora Matricial de Impacto 9 Pines (Dot Matrix) 2C-MP76-01
- Tipo de Impresión : Impresión de Impacto de 9 Pines
- Interface: USB
- Sierra Corte Manual
- Cash Drawer Port
- Ancho de Papel: 75.5± 0.5mm
- Alto de Papel: 75mm (Max)
- Impresión para 1 Original y 2 Copias
- Resolución : 84dpi (8dots/mm)
- Velocidad Impresión: 4.5 Líneas por segundo
- Power Input: AC 110V/240V,50~60Hz
- Power Output: DC 24V/2.5A
- Comandos Compatible: ESC/POS
- Compatible Con: Windows, Ubuntu, Linux, Mac OS
- SDK disponible para Windows y Android
- Brand New con 6 meses de Garantía

DESCRIPCIÓN TÉCNICA

Printer Dimension	230mm (L) × 150mm (W) × 138mm (H)
Net Weight	1.46Kg
Printing Method	9 Pins Impact Dot Matrix
Printing Speed	4.5 Lines per Second
Resolution	84 dpi
Max Printing Width	63.5mm
Media Type	Paper
Paper Width	75.5± 0.5mm
Paper Thickness	0.06mm-0.085mm
Paper Roll Diameter	80mm (Max)
Paper Supply Method	Friction feed
Sensor	Paper end sensor, black mark sensor, cover open sensor
Drawer Port	1 Port - DC 24V

Memory	NV Flash 64K, Input Buffer 32K
Mechanism Print Life	10 Million lines
Interface	USB
Emulation	ESC/POS
Driver	Windows, Linux, Mac OS
Utility	Windows
SDK	Windows, Android
Power Supply Input	AC 110V/240V,50~60Hz (Adapter)
Power Supply Output	DC 24V/2.5A
Operating Temperature	0°C to 45°C
Operating Humidity	10~80%
Storage Temperature	-10° to 60°C
Storage Humidity	10~90%